

CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS
CLASS 16 1101 - 16 1181
All the electrical components are Recognized or Certified UL or CSA,
and qualify for all Applicable Requirements CAN/CSA-C 22.2 No.243 and UL STD No.1017

Characteristics



Continuous Duty




Detachable Tank



Dry Recovery



HEPA Filter Available
HEPA - Optional



ULPA Filter Available
ULPA - Optional



Pharma Applications



Cleanroom Compatible



- HEPA Filter - Optional with an efficiency of 99.995% on 0.3 micron. Tested: IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility.
- ULPA Filter - With an efficiency of 99.999% on 0.12 micron. Tested: IEST-RP-CC001. Filtration efficiency of 99.9995% on 0.18 micron. Tested: IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility - Optional
- *Cleanroom compatible with ISO Class 4 (former Class 10)
- Designed to be attached to process machines and for general cleanup in the Food Industry
- Can also be used for the recovery of Tablets in the Pharmaceutical Industry.
- Continuous Duty Single or 3-Phase motor · mounted vertically
- Manual Filter Shaker (MFS) system.
- Available in a fixed or mobile unit
- For dry recovery only
- Available versions: Stainless Steel, White-Powder Coated, Stainless Steel & White-Powder Coated
- Vertical mounting for areas with space constraints.
- Equipped with 4 wheels for easy maneuverability

Specifications

CD-2600 CR (MFS) SERIES	111307A1	111307A2	111307A4	111307A5	111308A1	111308A2
Model Name	CD-2600 CR (MFS) - P/C & S/S	CD-2600 CR (MFS) - P/C & S/S	CD-2600 CR (MFS) - P/C & S/S	CD-2600 CR (MFS) - P/C & S/S	CD-2600 CR (MFS) - P/C & S/S	CD-2600 CR (MFS) - P/C & S/S
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes	Yes
Voltage	460 V	230 V	230 V	575 V	460 V	230 V
Hertz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Three	Three	Single	Three	Three	Three
Wattage	1900 W	1900 W	1900 W	1900 W	2600 W	2600 W
Power	2.5 HP	2.5 HP	2.5 HP	2.5 HP	3.5 HP	3.5 HP
Amperage	4 amps.	7 amps.	7.2 amps.	2.6 amps.	4.7 amps.	9.4 amps.
Air Flow	148 CFM	148 CFM	140 CFM	148 CFM	219 CFM	219 CFM
Vacuum Pressure	140 " H ₂ O	140 " H ₂ O	111+ " H ₂ O	140 " H ₂ O	145 " H ₂ O	145 " H ₂ O
VRV Setting	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O
Sound Level	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)
Plug Type	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
Suction Inlet	2 "	2 "	2 "	2 "	2 "	2 "
Cart Type	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
Dry Recovery - Tank	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal
Length	26 "	26 "	26 "	26 "	26 "	26 "
Width	20 "	20 "	20 "	20 "	20 "	20 "
Weight (Vacuum Only)	247 lbs.	247 lbs.	247 lbs.	247 lbs.	247 lbs.	247 lbs.
Height	75 "	75 "	75 "	75 "	75 "	75 "
Cord Length	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.
CD-2600 CR (MFS) SERIES	111308A5	111460A1	111460A2	111460A4	111460A5	111464A1
Model Name	CD-2600 CR (MFS) - P/C & S/S	CD-2600 CR (MFS) - STAINLESS STEEL	CD-2600 CR (MFS) - STAINLESS STEEL	CD-2600 CR (MFS) - STAINLESS STEEL	CD-2600 CR (MFS) - STAINLESS STEEL	CD-2600 CR (MFS) - STAINLESS STEEL
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes	Yes
Voltage	575 V	460 V	230 V	230 V	575 V	460 V
Hertz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Three	Three	Three	Single	Three	Three
Wattage	2600 W	1900 W	1900 W	1900 W	1900 W	2600 W
Power	3.5 HP	2.5 HP	2.5 HP	2.5 HP	2.5 HP	3.5 HP
Amperage	4 amps.	4 amps.	7 amps.	7.2 amps.	2.6 amps.	4.7 amps.
Air Flow	219 CFM	148 CFM	148 CFM	140 CFM	148 CFM	219 CFM
Vacuum Pressure	145 " H ₂ O	140 " H ₂ O	140 " H ₂ O	111+ " H ₂ O	140 " H ₂ O	145 " H ₂ O

Tiger-Vac Inc.
11 SW 12th Ave #112
Dania, FL 33004
USA

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: 1-800-668-4437 (954-925-3625)
Fax: 1-800-668-4439 (954-925-3626)

Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com

VRV Setting	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O
Sound Level	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)
Plug Type	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
Suction Inlet	2 "	2 "	2 "	2 "	2 "	2 "
Cart Type	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
Dry Recovery - Tank	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal
Length	26 "	26 "	26 "	26 "	26 "	26 "
Width	20 "	20 "	20 "	20 "	20 "	20 "
Weight (Vacuum Only)	247 lbs.	247 lbs.	247 lbs.	247 lbs.	247 lbs.	247 lbs.
Height	75 "	75 "	75 "	75 "	75 "	75 "
Cord Length	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.

CD-2600 CR (MFS) SERIES	111464A2	111464A5
Model Name	CD-2600 CR (MFS) - STAINLESS STEEL	CD-2600 CR (MFS) - STAINLESS STEEL
Type (Powerhead)	Electric	Electric
TEFC Motor	Yes	Yes
Voltage	230 V	575 V
Hertz	60 Hz	60 Hz
Phase	Three	Three
Wattage	2600 W	2600 W
Power	3.5 HP	3.5 HP
Amperage	9.4 amps.	4 amps.
Air Flow	219 CFM	219 CFM
Vacuum Pressure	145 " H ₂ O	145 " H ₂ O
VRV Setting	110 " H ₂ O	110 " H ₂ O
Sound Level	68 dB(A)	68 dB(A)
Plug Type	Not Included	Not Included
Suction Inlet	2 "	2 "
Cart Type	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
Dry Recovery - Tank	9.5 Gal	9.5 Gal
Length	26 "	26 "
Width	20 "	20 "
Weight (Vacuum Only)	247 lbs.	247 lbs.
Height	75 "	75 "
Cord Length	50 ft.	50 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



CD-2600 Next to average sized man



CD-2600 Rear View



CD-2600 with Recovery Tank removed



HEPA Filter - Optional