

DM40 WD - PROFESSIONAL WET & DRY



SHIPYARDS



BUILDING AND CONSTRUCTION



CLEANING CONTRACTORS



VEHICLE - TRANSPORT CLEANING



- ✓ Compact and mobile
- ✓ Heavy duty steel construction
- ✓ Complete steel construction
- ✓ Three powerful by pass motors with independent cooling



SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	3,45
Electrical protection	IP	F
Max waterlift	mmH2O	2500
Max air flow	m³/h	540
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	76



FILTRATION UNIT

Filter Type		Bag
Surface - Diameter	cm²-mm	8.000-500
Material - Efficiency	IEC 60335-2-69	Polyester - L



COLLECTION UNIT

Discharge system		Nuovo valore
Capacity	lt.	120



VOLUME

Dimensions	cm	68x63x125h
Weight	kg	50



SUCTION UNIT

The suction is provided by three by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



FILTRATION UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.



COLLECTION UNIT

Thanks to a discharge valve, it is possible to easily and safely empty the container. The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.



OPTIONALS

✓ STAINLESS STEEL COLLECTION TANK