



EXP1 Models Certified for:  
Class I, Division 1, Group D T3C and Class II, Division 1,  
Groups E, F and G



Ex d IIA T4 Gb  
Ex t IIIC T120°C Db IP65  
**IECEx LCI 10.0039**



**GUARANTEED** for the Safe Recovery  
of Combustible/Conductive Dusts and Flammable Liquids


**ESD Safe** Vacuum Cleaners for Hazardous Locations are  
designed to prevent ignition hazards.  
We use metal parts or Static Dissipative Powder Coating to  
prevent Electrostatic Discharge (ESD)



### Characteristics



Explosion Proof



Less than 10  
ohms



HEPA - Included



High Efficiency



Cleanroom  
Compatible



Pharma  
Applications



Wet and Dry  
Recovery



SS 304



SD Accessories -  
Included

- Legally certified explosion proof/dust ignition proof.
- Less than 10 Ohms of resistivity.
- HEPA Filter - Included with an efficiency of 99.995% on 0.3 micron. Tested: IEST RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility.
- \*Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the pharmaceutical industry
- For general cleanup in hazardous locations
- Single Phase explosion proof / dust ignition proof motor.
- For wet and dry recovery
- All Stainless Steel SAE 304 construction
- SD\* Polyliner and clip available for the easy and safe disposal of recovered materials.
- Mounted on an SD\* 4-wheel dolly for easy maneuverability. Dolly has SD\* conductive wheels
- Includes a complete static dissipative tool kit

## Specifications

EXP1-10/15 (4W) RE SERIES	110249A	110251A
<b>Model Name</b>	EXP1-10 (4W) RE HEPA	EXP1-15 (4W) RE HEPA
<b>Type (Powerhead)</b>	Electric	Electric
<b>TEFC Motor</b>	Yes	Yes
<b>Voltage</b>	120 V	120 V
<b>Hertz</b>	60 Hz	60 Hz
<b>Phase</b>	Single	Single
<b>Wattage</b>	1000 W	1000 W
<b>Power</b>	1.3 HP	1.3 HP
<b>Amperage</b>	9 amps.	9 amps.
<b>Air Flow</b>	132 CFM	132 CFM
<b>Vacuum Pressure</b>	69 " H <sub>2</sub> O	69 " H <sub>2</sub> O
<b>Sound Level</b>	78/85 dB(A)	78/85 dB(A)
<b>Plug Type</b>	Not Included	Not Included
<b>Suction Inlet</b>	1.5 "	1.5 "
<b>Cart Type</b>	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
<b>Filter Cleaning</b>	None	None
<b>Dry Recovery - Tank</b>	6 Gal	10 Gal
<b>Wet Recovery Capacity</b>	7.5 Gal	12.5 Gal
<b>Length</b>	19 "	19 "
<b>Width</b>	18 "	18 "
<b>Weight (Vacuum Only)</b>	82 lbs.	68 lbs.
<b>Height</b>	33 "	38 "
<b>Cord Length</b>	50 ft.	50 ft.

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



EXP1-15 (4W)



Ø1.5 (Ø38mm) Static Dissipative Tools and Accessories - Included



HEPA Filter - Included