

A small unit that packs a big punch!

Introducing the new **OSPREYFRANK** range

- Compact but tough with robust stainless steel body
- Industrial quality steam socket
- Professional boiler with continuous boiler refill
- Twin external detergent facility for ease of change
- Steam volume regulator
- Front locking castors
- Simple and clear operation
- Cost effective
- Environmentally friendly
- Ideal for small/medium manufacturing/ engineering facilities



SF6 Machine Specification			
Power Supply	400 Volt 50Hz 16 Amp	Cable Length	5 metres
Maximum Power	5,500 Watt	Machine Dimensions (W x D x H) cm	50 x 82.5 x 100
Steam Pressure	10 Bar	Net Weight	32Kg
Boiler Capacity / Boiler Material	3.6 Litres / RVS AISI 304	Shipping Weight	39Kg
Detergent Capacity	2 x 5 Litre	Certification/Marking	CE, IPX4
Heating Up Time	Approx. 6 minutes	Max. Boiler Temperature	185°C
Steam production	150 gr./min	Adjustable Output Regulator	Yes
Autonomy	Continuous Operation	Indicator for Lack of Water	Yes

SF6 Standard Steam Only Accessories			
	Flexible 4m Hose A03053		Industrial Lance 400mm Hooked Nozzle A03125 (A03150 Required)
	Industrial Lance 900mm hooked nozzle A03131 (A03150 Required)		Industrial Squeegee 350mm A03133
	Nylon Detail Brush A03081		Copper Detail Brush A03082
	Stainless Steel Detail Brush A03083		60mm Round Nylon Brush A03074
	60mm Round Copper Brush A03075		60mm Round Stainless Steel Brush A03076
	55mm Scotch brite round pad A03145		1.5mm Nozzle Tip for Industrial Lances A03150
	Accessory Bag A00903		Safety Goggles A00096
	Safety Gloves A00097		

For More Information... T: 01242 513 123 F: 01242 518 666 E: info@ospreydc.com W: www.ospreydc.com